



## Overview

- 4MP IR
- True WDR 120dB
- 4.0mm lens
- H.265
- IP67, IK10 rated








## Technical Specifications

Device	
Image Sensor:	1/3" Progressive Scan CMOS
Min Illumination:	Colour: 0.01Lux (F2.0, AGC ON)   0Lux with IR
Shutter Time:	Auto/Manual, 1 ~ 1/100000s
Lens:	4.0mm@F2.0
WDR:	120dB
Angle of View :	H: 82.0°, V: 41.6°, O: 100.9°
Angle Adjustment:	Pan: 3° ~ 360° Tilt: 0° ~ 68° Rotate: 3° ~ 360°
3-Axis Adjustment :	Yes
Day & Night:	IR-Cut Filter with Auto Switch (ICR)
IR Range:	Up to 30m (98ft) IR range
Compression Standard	
Video Compression:	Ultra 265, H.265, H.264, MJPEG
Video Bit Rate:	128 Kbps~16 Mbps
Tri-Stream:	Yes
Analytics:	Intrusion, Human Body Detection, Motion Detection, Tampering Alarm, Audio Detection
Image	
Max. Image Resolution:	2688 x 1520
Frame Rate:	30fps (2688 x 1520)
ROI Codec:	Up to 2 Areas
Image Setting:	White Balance, Digital Noise Reduction, Smart IR, Flip, HLC, BLC



## Technical Specifications

<b>Network</b>	
Alarm Channels:	1 Channel In   1 Channel Out
Protocols:	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
<b>Interface</b>	
Communication Interface:	1 RJ45 10M/100M Base-TX Ethernet
System Compatibility:	ONVIF (Profile S, Profile G, Profile T), API
Local Storage:	Micro SD, up to 256GB
Audio:	Input: Impedance 35kΩ; Amplitude 2V [p-p] Output: Impedance 600Ω; Amplitude 2V [p-p]
<b>General</b>	
Operating Conditions:	Temperature: -35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (Non-Condensing)
Power Consumption:	Max 5.5W
Power Supply:	DC 12V±25%, PoE (IEEE 802.3af)
Weather Proof Rating:	IP67
Vandal Resistant:	IK10
Dimensions:	Φ108.7 x 81.1mm (Ø4.3" x 3.2")
Weight:	0.45kg (0.99lb)
Software:	Includes Video Insight VMS License
Warranty:	4 Year Advanced Replacement
<b>Accessories</b>	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>M-JB-MINI</p>  </div> <div style="text-align: center;"> <p>M-WM-JB-MINI</p>  </div> <div style="text-align: center;"> <p>M-PM</p>  </div> </div> <div style="display: flex; justify-content: space-around; align-items: flex-start; margin-top: 20px;"> <div style="text-align: center;"> <p>M-Pendant-Ex</p>  </div> <div style="text-align: center;"> <p>M-Pendant</p>  </div> </div>